



DAIKEN NDF CO-ORDINATE SERIES Mineral Fibre Acoustic Suspended Ceiling Tile



Daiken Co-Ordinate Series Mineral Fibre Acoustic ceiling tiles have a white non-directional fissured scored board surface.

- The Coordinate tile has a medium Noise Reduction Coefficient and medium Ceiling Attenuation Class to help reduce reverberation time and to prevent sound transfer through the ceiling plenum
- It is a higher range product with good detailing. Recommended for Commercial application where a point of difference is required.
- The refined Daiken Ceiling Tile manufacturing process offers clean precise scoring lines.
- Daiken Mineral Fibre Acoustic Ceiling materials are not only non-combustible, but also less likely to emit gas or smoke, or to melt, break or become deformed under normal fire conditions.
- 30 year lifetime system warranty to withstand conditions up to 40° - 99% relative humidity without visible sag when used with a T&R Interior Systems brand suspension system



EMISSIONS, SUSTAINABILITY AND THE ENVIRONMENT - For Green Star rated projects, Daiken mineral fibre tiles were independently verified and meet the Greenguard Emission Certificate standard.

Wellington Head Office
12 Glover St, Ngauranga
Wellington 6035
PO Box 38533
Wellington Mail Centre 5045
/t/ 04 499 5915

Auckland
19 - 21 Fairfax Ave,
Penrose, Auckland 1061
PO Box 112360,
Penrose, Auckland 1642
/t/ 09 571 0395


Christchurch
69 Disraeli St, Addington
Christchurch 8023
PO Box 7197
Christchurch 8240
/t/ 03 366 2507



DAIKEN NDF CO-ORDINATE SERIES

Mineral Fibre Acoustic Suspended Ceiling Tile




TEST DESCRIPTION	RESULT	TEST METHOD
Noise Reduction Coefficient	NRC 0.55 -0.60	ASTM C 423
Ceiling Attenuation Class	CAC36	ASTM E 413
Weight	4.2kg/m ²	
Light Reflectance	LR 1 (over 75%)	ASTM C 523
Fire Test	 Group 1 – S	BRANZ Cone Calorimeter NZBC C/AS1 – AS27
Relative Humidity	RH 99%	
Thermal Conductivity	0.045 kcal/mh ° C	JIS A 1412

- SIZE**
 - 15mm Depth x [1200 x 600] Co-ordinate 10, 40
 - 15mm Depth x [1200 x 600] Co-ordinate 20, 41
 - To suit 15 or 24 mm grid patterns


- COLOUR**

- EDGE DETAIL**




– indent only
Co-ordinate 10



Co-ordinate 20



Co-ordinate 41



Wellington Head Office
 12 Glover St, Ngauranga
 Wellington 6035
 PO Box 38533
 Wellington Mail Centre 5045
 /t/ 04 499 5915

Auckland
 19 - 21 Fairfax Ave,
 Penrose, Auckland 1061
 PO Box 112360,
 Penrose, Auckland 1642
 /t/ 09 571 0395

Christchurch
 69 Disraeli St, Addington
 Christchurch 8023
 PO Box 7197
 Christchurch 8240
 /t/ 03 366 2507