







MAINTENANCE GUIDE

FLOC 3D

ALWAYS WEAR GLOVES WHEN HANDLING PANELS



CLEANING

- Dust and loose dirt can be easily removed from the face of the panels by the use of a soft brush or with a vacuum cleaner. A vacuum cleaner fitted with an upholstery attachment is the most suitable. It is recommended that when brushing or vacuuming it is done in one direction only for best results. Loose dirt may involve such types as mud or grass.
- For pen and ink stains lightly sponge with household woolwash and blot until dry. Apply sparingly, as the substance may have an adverse effect.
- More general soiling can be cleaned with a damp cloth or sponge. These can be dampened in a clean water and mild woolwash solution. Avoid using an excessive amount of water. Again wipe the panels in one direction only. After this process any residue can be cleaned off with a clean cloth or sponge lightly dampened in clean water. Mop up excess as soon as possible with a sponge or cloth.
- In the case of sticky substances such as gum or glue etc, it can be removed with a knife edge or appropriate instrument. If gum surface is too soft, freeze with ice cubes and scrape away while cold.
- Removal of water based paint stains can be facilitated with glycerine or petroleum jelly.

Abrasive cleaners must not be used.

Broken, or excessively soiled panels should be replaced.

Painting of the soiled or discoloured panels should be a last resort as this process will dramatically reduce the acoustic performance of the wall panels.

For further assistance please contact your local T&R Interior Systems.