

CARE AND MAINTENANCE GUIDE

RAISED ACCESS FLOOR

CLEANING GUIDELINES

High Pressure Laminate floor tiles are easy to maintain.

- Dry mop or vacuum regularly. Damp mop with a mild detergent when necessary.
- Do not flood floor with water or cleaning agents from overly saturated mops.
- Do not coat floor with oil and chemicals.
- Spot clean stubborn stains with a non-flammable organic cleaner. Most organic solvents will dissolve the adhesive used to attach laminate to the panel surface. Make sure that the cleaner does not get into cracks between the support panel and the laminate where it could adversely affect the bond.
- Do not clean with steel wool or abrasives of any kind. Do not wax, buff or polish the floor.
- Needs no sealer, coating, waxing or stripping. No vigorous cleaning or strong cleaning agents required.
- Stain resistant to inks, chemicals and cleaning agents.
- Spilled liquids wipe up easily. Stubborn stains can be easily spot cleaned using a nonflammable solvent.
- Non-Static; does not attract dust.
- Keeping the floor clean ensures maximum life.

NB: The floor will suffer permanent damage from plaster, mortar and paint splashes - Protect if splashes occur- Immediately wash down with water - do not allow splashes to harden. Use cleaning methods described above and do not use solvents or abrasive cleaners.

For further assistance please contact your local T&R Interior Systems.